

## SHUTTLE 2+2 TXT®



Transport up to four people in the stylish and comfortable E-Z-GO® Shuttle 2+2 TXT®. Choose from the gas-powered model, featuring a best-in-class 13 hp Kawasaki® engine that delivers excellent power and fuel economy, or the zero-emissions 48-volt electric model with enhanced regenerative braking for longer range between charges. The Shuttle 2+2 TXT is perfectly suited for transporting the family around the neighborhood or golf community.

EXCELLENCE IN MOTION

**EZGO**®

A Textron Company

# SHUTTLE 2+2 TXT

## GREEN FACTORS

- Electric model features a quiet, energy-efficient 48-volt drivetrain with enhanced regenerative braking
- Gas model features a single-cylinder engine with a hemispheric combustion chamber for increased fuel mileage and reduced emissions
- Foam seating made of 100% recycled materials
- Sloped surface design requires less water when cleaning
- Repairable seat components minimize landfill usage
- Recyclable plastic components



## ELECTRIC

BODY & CHASSIS	
Frame	Welded steel with powder-coat paint
Body & Finish	Injection-molded TPO
Standard Color	Champagne
DIMENSIONS	
Overall Length	103.0 in (292 cm)
Overall Width	47.0 in (119 cm)
Overall Height (no canopy)	46.5 in (118 cm) (top of steering wheel)
Overall Height (with canopy)	68.0 in (173 cm) (top of sun canopy)
Wheel Base	66.0 in (168 cm)
Front Wheel Track	34.0 in (86 cm)
Rear Wheel Track	38.5 in (97 cm)
Ground Clearance (at differential)	4.5 in (11 cm)
POWER	
Power Source	48-volt DC
Motor Type	Shunt wound
Horsepower	3.0 hp (2.2 kW) continuous
Electric System	48-volt
Batteries (qty/type)	Six, 8-volt deep cycle
Battery Charger	48 VDC PowerWise™ OE, 120 VAC, UL/CSA
Speed Controller	250-amp solid-state controller
Drivetrain	Motor shaft direct drive
Transaxle	Differential with helical gears
Gear Selection	Dash-mounted forward-neutral-reverse
Rear Axle Ratio	12.44:1
PERFORMANCE	
Seating Capacity	4-person
Weight without Batteries	642 lb (293 kg)
Curb Weight	1,020 lb (463 kg)
Vehicle Load Capacity	800 lb (363 kg)

PERFORMANCE CONT.	
Outside Clearance Circle	19.0 ft (5.8 m)
Ground Speed (level ground)	14.8 mph ± 0.5 mph (23.8 kph ± 0.8 kph)
STEERING & SUSPENSION	
Steering	Self-compensating rack and pinion
Front Suspension	Leaf springs with hydraulic shock absorbers
Rear Suspension	Leaf springs with hydraulic shock absorbers
Service Brake	Rear wheel mechanical self-adjusting drum
Parking Brake	Self-compensating, single-point engagement
Front Tires	Hole-in-One 18 x 8.50-8 (4-ply rated)
Rear Tires	Hole-in-One 18 x 8.50-8 (4-ply rated)
OTHER STANDARD FEATURES	
Headlights, Taillights, Brake Lights, Horn, State of Charge Meter, Four Center-Mounted Cup Holders, DC-to-DC Converter	



FRONT



SIDE



BACK

## GAS

BODY & CHASSIS	
Frame	Welded steel with powder-coat paint
Body & Finish	Injection-molded TPO
Standard Color	Champagne
DIMENSIONS	
Overall Length	103.0 in (292 cm)
Overall Width	47.0 in (119 cm)
Overall Height (no canopy)	46.5 in (118 cm) (top of steering wheel)
Overall Height (with canopy)	68.0 in (173 cm) (top of sun canopy)
Wheel Base	66.0 in (168 cm)
Front Wheel Track	34.0 in (86 cm)
Rear Wheel Track	38.5 in (97 cm)
Ground Clearance (at differential)	4.25 in (10.8 cm)
POWER	
Power Source	4-cycle 24.5 cu in (401 cc) low-emissions
Valve Train	Single-cylinder OHV
Horsepower (kW)	13 hp (9.7 kW) exceeds SAE J1940 Std.
Electric System	Starter/generator, solid-state regulator
Batteries (qty/type)	One, 12-volt maintenance-free
Air Cleaner	Industrial-rated dry filter
Lubrication	Pressurized oil system
Oil Filter	Spin on
Cooling System	Air-cooled
Fuel Capacity	5.8 gallon (22.0 L) tank
Drive Train	Continuously variable transmission (CVT)
Transaxle	Differential with helical gears
Gear Selection	Forward-reverse
Rear Axle Ratio	11.42:1 (forward) 15.78:1 (reverse)

PERFORMANCE	
Seating Capacity	4-person
Dry Weight	845 lb (383 kg)
Curb Weight	880 lb (400 kg)
Vehicle Load Capacity	800 lb (360 kg)
Outside Clearance Circle	19.0 ft (5.8 m)
Ground Speed (level ground)	14.0 mph $\pm$ 0.5 mph (22.5 kph $\pm$ 0.8 kph)
STEERING & SUSPENSION	
Steering	Self-compensating rack and pinion
Front Suspension	Leaf springs with hydraulic shock absorbers
Rear Suspension	Leaf springs with hydraulic shock absorbers
Service Brake	Rear wheel mechanical self-adjusting drum
Parking Brake	Self-compensating, single-point engagement
Front Tires	Hole-in-One 18 x 8.50 - 8 (4-ply rated)
Rear Tires	Hole-in-One 18 x 8.50 - 8 (4-ply rated)
OTHER STANDARD FEATURES	
Headlights, Taillights, Brake Lights, Horn, Fuel Gauge, Four Center-Mounted Cup Holders	

To learn more about the Shuttle 2+2 TXT or to receive a custom quote from your local E-Z-GO dealer, call: (800) 241-5855 or visit [www.ezgo.com](http://www.ezgo.com) today.

## SHUTTLE 2+2 TXT OPTIONS & ACCESSORIES

APPEARANCE	
Vehicle Color	<ul style="list-style-type: none"> <li>• Orange • Cloud Grey • Patriot Blue • Inferno Red • Steel Blue • Black</li> <li>• Metallic Charcoal • Yellow • White • Flame Red • Electric Blue • Platinum</li> <li>• Champagne • Hunter Green • (custom colors available)</li> </ul>
Seat Color	<ul style="list-style-type: none"> <li>• Oyster • Tan • Grey • (custom colors available)</li> </ul>
Pinstripes	<ul style="list-style-type: none"> <li>• Gold • Dark Green • White • Black • Red • Burgundy • (custom colors available)</li> </ul>
Weather Protection	<ul style="list-style-type: none"> <li>• Sun Canopy: White, Tan</li> <li>• Weather Enclosure: 3-Sided, 4-Sided</li> <li>• Windshield: Clear Flat, Clear Fold Down</li> </ul>
ELECTRICAL	
Battery Charger (Electric only)	<ul style="list-style-type: none"> <li>• 48 V PowerWise™ QE, 18 foot (5.5 m) DC Cord</li> <li>• World Charger QE 48 V 10 foot (3.0 m) DC Cord</li> <li>• World Charger QE 48 V 18 foot (5.5 m) DC Cord</li> </ul>
Key Switch	<ul style="list-style-type: none"> <li>• Unique Group • Unique Individual</li> </ul>
Programmable Speed Modes (Electric only)	<ul style="list-style-type: none"> <li>• Coastal • Mild Hill • Steep Hill • Airport</li> </ul>
Other Electrical	<ul style="list-style-type: none"> <li>• Battery Fill System Nozzle</li> <li>• Battery Fill System</li> <li>• State of Charge Meter</li> <li>• Non-Standard Battery Option</li> <li>• Hour Meter</li> <li>• Handheld Diagnostic Unit (Electric only)</li> <li>• Turn Signals with 4-Way Flashers</li> </ul>
TIRES & WHEELS	
Tires	<ul style="list-style-type: none"> <li>• USA Trail 18 x 8.50-8 (load range C)</li> <li>• Turf Saver 18 x 8.50-8 (load range B) (rear tires only)</li> <li>• Tour Max 18 x 8.50-10 on alloy wheels</li> <li>• Speed Racer 18 x 10-10 on "Diamond" pattern aluminum wheels</li> </ul>
Wheel Covers	<ul style="list-style-type: none"> <li>• Silver Spoke • Platinum Spoke</li> </ul>
PERFORMANCE	
Other Options/Enhancements	<ul style="list-style-type: none"> <li>• Ash Tray • Differential Guard • Heavy-Duty Rear Suspension</li> <li>• Cleat Cleaner • Message Holder • Rearview Mirror</li> <li>• Golf Bag Attachment for Two (2) Bags • High Altitude Setting (Gas only)</li> <li>• CE Compliance Kit • Convertible Cargo Carrier for Rear Seat (Gas only)</li> </ul>



PLATINUM SPOKE  
WHEEL COVERS



STATE OF CHARGE  
METER



HEADLIGHT



FOUR CENTER-MOUNTED  
CUP HOLDERS

To learn more about the Shuttle 2+2 TXT or to receive a custom quote from your local E-Z-GO dealer, call: (800) 241-5855 or visit [www.ezgo.com](http://www.ezgo.com) today.



1451 Marvin Griffin Road, Augusta, GA 30906  
 (800) 241-5855 | Fax (706) 796-4540 | [www.ezgo.com](http://www.ezgo.com)  
 e-mail: [ezgo@textron.com](mailto:ezgo@textron.com) | ©2010 E-Z-GO Division of Textron Inc.  
 \*Features and specifications are subject to change without notice.

82243-G1



A Textron Company